



US009638405B2

(12) **United States Patent**
Hobson

(10) **Patent No.:** **US 9,638,405 B2**
(45) **Date of Patent:** **May 2, 2017**

(54) **ADJUSTABLE PHOTOCONTROL
MOUNTING ASSEMBLY**

(71) Applicant: **Cree, Inc.**, Durham, NC (US)

(72) Inventor: **Charles O. Hobson**, Waterford, WI
(US)

(73) Assignee: **Cree, Inc.**, Durham, NC (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 262 days.

(21) Appl. No.: **14/209,390**

(22) Filed: **Mar. 13, 2014**

(65) **Prior Publication Data**

US 2015/0260377 A1 Sep. 17, 2015

(51) **Int. Cl.**

H01R 4/50 (2006.01)

F21V 23/04 (2006.01)

F21V 17/02 (2006.01)

(52) **U.S. Cl.**

CPC **F21V 23/0464** (2013.01); **F21V 17/02**
(2013.01); **Y10T 29/49826** (2015.01)

(58) **Field of Classification Search**

CPC F21V 23/0464; F21V 17/02; Y10T
29/49826; H04N 7/185; G01J 1/02; G01J
1/0271; G01J 1/04

USPC 439/337

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

774,250 A 11/1904 Hubbell
903,768 A 11/1908 Platt

2,941,182 A 6/1960 Heller
2,970,222 A 1/1961 Husby et al.
3,031,582 A 4/1962 Benner et al.
3,083,347 A 3/1963 Fahey, Jr.
3,123,423 A 3/1964 Schmitt
3,343,852 A 9/1967 Blight et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CN 202995464 U 6/2013
CN 202995489 U 6/2013

(Continued)

OTHER PUBLICATIONS

Hubbell brochure titled "Twist-Lock Wiring Devices and Safety
Enclosures" 28 pages, Copyright 1998.

(Continued)

Primary Examiner — Jean F Duverne

(74) *Attorney, Agent, or Firm* — Jansson Munger
McKinley & Kirby Ltd.

(57)

ABSTRACT

An assembly for connecting and holding a photocontrol with respect to a light fixture. The assembly includes a support member and a photocontrol receptacle over and secured with respect to the support member. The support member is on an exterior surface of a light-fixture housing at an opening formed in the housing. The photocontrol receptacle is rotatable about the support member for angular photocontrol adjustment on the light fixture. The support member is fixed with respect to the exterior surface of the light-fixture housing. The receptacle has an engagement portion rotatably engaging the support member, thereby holding the receptacle with respect to the light-fixture housing while permitting rotation of the receptacle with respect thereto. Another aspect is a related method for connecting and holding a photocontrol with respect to a light fixture.

25 Claims, 8 Drawing Sheets

